



PRODUCT DATA SHEET

GIANT DEXRON III

High Performance Multipurpose Automatic Transmission Fluid

DESCRIPTION

GIANT DEXRON III is a high performance, multipurpose automatic transmission fluid (ATF) for modern passenger cars and light trucks.

GIANT DEXRON III is suitable for use in most GM and Ford applications, and all Allison C4 applications, and any other application calling for use of DIIH/M quality ATF.

PERFORMANCE STANDARDS

- Allison C4
- GM Dexron IIIH
- Ford Mercon
- Caterpillar TO-2

BENEFITS

- Provides excellent oxidation stability and deposit control under very high temperature and severe operating conditions.
- Exhibits excellent anti-wear properties.
- Provides good antifoam properties.
- Maintains good antirust and anticorrosion properties.
- Provides minimum evaporation loss due to low volatility of the fluid.
- Provides protection against wear and leakage due to its compatibility with a wide range of elastomers and metals.

TYPICAL APPLICATIONS

GIANT DEXRON III is recommended for filling and topping up of automatic transmissions and power steering systems requiring GM D-III and Ford M specifications.

It is also recommended for on highway and off highway use in Allison heavy duty automatic transmissions.

TYPICAL PROPERTIES

Specific Gravity	ASTM D-1298	0.889
Kinematic Viscosity, cSt @ 40°C	ASTM D-445	157.0
Kinematic Viscosity, cSt @ 100°C	ASTM D-445	18.3
Viscosity Index	ASTM D-2270	118
Pour Point, °C	ASTM D-97	-15
Flash Point COC, °C	ASTM D-92	220