



## PRODUCT DATA SHEET

### GIANT Small Engine Red SAE 30

Hydrocracked SAE 30 Small Engine Oil

#### DESCRIPTION

GIANT Small Engine Red SAE 30 is a hydrocracked SAE 30 small engine oil specifically designed for use small 4-stroke petrol engines. It is a premium formulation to exceed the specifications of API SG with excellent protection against wear, rust and corrosion, as well as minimising the formation of sludge and varnish deposits. It is shear- and thermal-stable under a wide range of operating temperatures.

#### BENEFITS

- Premium-quality oil that meets or exceeds the warranty requirements of most manufacturers for 4-stroke small engines with a specification for API SG.
- Superb anti-wear, detergency and anti-oxidant properties.
- Excellent anti-foaming & anti-corrosion properties.
- Keeps the engine clean and in good condition, even while operating at high temperatures.
- Hydrocracked oil with high Viscosity Index to counter the variance of viscosities under different temperatures, providing ample protection even at higher temperatures.
- Better thermal stability and oxidation controls allow for extended drain intervals.

#### PERFORMANCE STANDARDS

- API SG/CD

#### TYPICAL APPLICATIONS

- Air or liquid-cooled small 4-stroke engines.
- Lawn mowers

#### TYPICAL PROPERTIES

SAE		30
Specific Gravity	ASTM D-4052	0.8648
Kinematic Viscosity, cSt @ 40°C	ASTM D-445	103.8
Kinematic Viscosity, cSt @ 100°C	ASTM D-445	12.5
Viscosity Index	ASTM D-2270	113
TBN, mgKOH/g	ASTM D-2896	7.9